

DATA SHEET

VR25112 WE202

Description	Rigid PVC Extrusion Compound
Colour	White
Application	General Purpose Profiles For Internal and External Use
Characteristics	High Impact. Easy Processing.
Form	Pellet
SDS No.	0

TYPICAL PROPERTIES

	Test Method	Units	Value
General Properties			
Density	EN ISO 1183-1 A	kg/m ³	1530
Vicat Softening Point	EN ISO 306 B50	°C	78.0
Mechanical Properties			
Flexural Modulus	EN ISO 178	MPa	2280
Flexural Strength	EN ISO 178	MPa	56.0
Tensile Stress at Yield (50mm/min)	EN ISO 527-1	MPa	46.9
Tensile Stress at Break (50mm/min)	EN ISO 527-1	MPa	28.7
Tensile Strain at Break (50mm/min)	EN ISO 527-1	%	19
Izod Impact Strength (23°C)	EN ISO 180/A	kJ/m ²	12
Other Properties			
Thermal Stability (200°C)	EN ISO 182-1	min	24

Issue 1 August 2016

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given, nor is to be implied with respect of such information. Users should make their own enquiries to determine the suitability of products for any particular application. Freedom from patents, copyright and registered designs cannot be assumed.

Registered Office
INEOS Compounds Aycliffe Limited
School Aycliffe Lane
Newton Aycliffe
Co Durham
DL5 6EA